Silencio 652S

Installation Guide

User manual / English
Инструкция за експлоатация / Български
安装说明 / 简体中文
快速安裝手冊 / 繁體中文
Uživatelská příručka / Čeština
Handbuch / Deutsch
Εγχειρίδιο χρήστη / Ελληνικά
Manual de Usuario / Español
Manuel de l'utilisateur / Français
Felhasználói kézikönyv / Magyar
Manuale d'uso / Italiano
ユーザーズマニュアル / 日本語
Handleiding / Nederlands
설치 안내 / korean
Kılavuzu / Türkçe
Instrukcja Użytkownika / Polski
Manual do Usuário / Português
Руководство пользователя / русский
Uputstvo za korišćenje / Srpski
Kullanım Kılavuzu / Türkçe

Asia Pacific - Cooler Master Technology Inc.
4th, No. 199-1, Zhongcheng Rd., Zhonghe Dist.,
New Taipei City 23586, Taiwan (R.O.C.)
Tel: +886-2-2225-3917
Service: eservice@coolermaster.com.cn

CHINA
Cooler Master China
5/F., Building B, No. 18, HeChang E. 4th Rd., Zhonghe,
Hui-Zhou City, Guang Dong Province, China
Tel: +86-752-2086-168
Service: eservice@coolermaster.com.cn

EUROPE
Cooler Master Europe B.V.
Hoogoorddreef 15 1101 BA Amsterdam
The Netherlands
Service: Support@coolermaster.nl

USA
Cooler Master USA
4620 Schaefer Ave, Chino CA 91710, USA
Service: support@coolermaster.com

Global Live Help: http://www.coolermaster.com/livehelp

1120000381 (Ver:1.0) (0316)

For the most updated information, please visit our official website: **http://www.coolermaster.com**

©2014 Cooler Master Technology Inc. All Rights Reserved.
All trademarks are registered to their respective owners.

CONTENTS

1. Specifications.....02
2. Fittings Pack.....03
3. I/O Function panel installation guide.....05
4. Diagram.....06
5. How to tinstrucve the side panel.....07
6. How to install the motherboard.....07
7. How to install the add-on cards.....08
8. How to install the power supply.....08
9. How to install a radiator 09
10. How to install the 5.25" device.....10
11. How to install the 3.5" / 2.5" device.....11
12. How to install or replace the case fan.....11
13. How to clean the dust filters 16
14. How to install the lock-buckle.....17
15. Completing installation.....17
16. Warranty information.....18

Specifications

Model	SSL-652-KWN1
Available color	Midnight Black
Material	SECC/Plastic
Dimensions (H/W/D)	220 x 507 x 508.6mm / 8.7 x 20 x 20 inch
Net Weight	10.7 kg / 23.5 lb
M/B Type	ATX, E-ATX
5.25" Drive Bays	3 (exposed)
3.5" Drive Bays	8 (hidden)
2.5" Drive Bays	10 (hidden), 7 in the HDD/SSD combo cages, 3 under the ODD cages.
I/O Panel	USB 3.0 x 2, USB 2.0 x 2, Audio x 1 (supports HD AC'97 / HD Audio) , Mic x 1, SD card reader (Class 10)
Expansion Slots	7
Air Cooling System	Top: 120/140mm fan x 2, or 180/200mm fan x 1 (optional) Rear: 120mm fan x 2 (included), 120/140mm fan x 1 (optional) Front: 120mm fan x 2 (optional), 140mm fan x 1 (included) Bottom: 120/140mm fan x 2 (optional) HDD cage: 120mm fan x 1 (optional)
Liquid Cooling System	Top: 240/280/360mm radiator (optional), requires an optional adapter. Rear: 120mm radiator (optional) Front: 240/280/360mm radiator (optional)
Power Supply	ATX power supply (Bottom)
Maximum Compatibility	VGA card length: 370mm / 14.6 inch (with HDD cage) 310mm / 12.2 inch (with SSD cage) CPU cooler height: 190mm / 7.4 inch CPU cooler height (Without 5.25 inch bay): 240mm / 9.4 inch

Product specifications are subject to change without notice.

型号	SSL-652-KWN1
颜色	午夜黑
材质	SECC/塑料
尺寸（宽 x 高 x 长）	220 x 507 x 508.6mm
净重	10.4 kg
支持规格	mini-ITX, ATX
5.25"托架	3 (外露)
3.5"托架	8 (隐藏)
2.5"托架	10 (隐藏) ，7 个在 HDD/SSD 组合笼架中，3 个在光驱笼架下。
I/O 面板	USB 3.0 x 2, USB 2.0 x 2, Audio x 1(支持AC'97 / HD Audio), Mic x 1, SD card reader (Class 10)
扩展槽	7 个
散热风扇支持	顶部：120/140mm 风扇 x 2，或 180 / 200mm 风扇 x 1（选配） 后部：120mm 风扇 x 2（已随附），120/140mm 风扇 x 1（选配） 前部：120mm 风扇 x 2（选配），140mm 风扇 x 1（已随附） 底部：120/140mm 风扇 x 2（选配） 硬盘笼架：120mm 风扇 x 1（选配）
液冷支持	顶部：240/280/360mm 散热器，支持选配转接架。 后部：120mm 散热器（选配） 前部：240/280/360mm 散热器（选配）
电源规格	ATX 电源（底部安装）
兼容性	显卡长度：370mm（带HDD笼架）/ 312mm（带SSD笼架） CPU 散热器高度：190mm（带HDD笼架）

* 产品规格如需更新恕不另行通知。

Silencio 652S

1. CPU cooler compatibility
Please ensure that your CPU cooler does NOT exceed 6.0 inch (152mm) height, if with side panel fan 6.3 inch (160mm) height, if without side panel fan.
2. Please ensure that your VGA card does NOT exceed 14.6 inch (370mm) in length, it will cause damage to the case and the graphics card.

Fittings Pack

Pics	Name	Qty	Used for
	#6 - 32*6 screw	8	Lock B/C, Lock 3.5" HDD
	#6 - 32*3/8 screw	4	HDD cage fan
	Stand-off socket	2	PU, P/ S fan
	Stand - off	10	M / B fan
	M/B screw	12	M / B fan
	#6 - 32*0 screw	7	HDD cage
	#6 - 32*4 screw	4	PSU
	Lock B/T	2	Side panel
	Case spacker	1	M / B Warning
	Cable tie	10	Cable management
	Anti-vibration pad	12	2.5" SSD
	M/B screw	12	2.5" SSD
	2.5" HDD adaptor	2	2.5" HDD
	Ø5*10 screw	8	Lock top fan Lock bottom fan
	M/B screw	40	ODD, 2.5" SSD
	Ø5*10.5 screw	4	Side fan
	stand-off	1	HDD cage

Silencio 652S

配件包

图片	名称	数量	用途
	#6 - 32*6 螺钉	8	锁扣B/C, 锁3.5"硬盘
	#6 - 32*3/8 螺钉	4	锁HDD 支架风扇
	铜柱螺丝	1	铜柱螺丝
	铜柱	10	固定主板
	M/PS 螺钉	12	特定板
	#6 - 32*0 螺钉	7	固定主板螺丝
	#6 - 32*4 螺钉	4	锁电源
	锁片	1	固定
	隔离垫	12	主板防震垫
	扎带	10	整理线材
	机箱垫	10	固定主板
	M/PS 螺钉	12	固定2.5"硬盘
	3.5"转换支架	2	固定3.5"硬盘
	螺钉	8	固定上盖风扇 固定下盖风扇
	M/PS 螺钉	40	锁光驱,固定2.5"硬盘
	螺钉	4	固定侧板风扇
	螺柱	1	固定HDD 支架

Silencio 652S

1. CPU cooler compatibility
Please ensure that your CPU cooler does NOT exceed 6.0 inch (152mm) height, if with side panel fan 6.3 inch (160mm) height, if without side panel fan.
2. Please ensure that your VGA card does NOT exceed 14.6 inch (370mm) in length, it will cause damage to the case and the graphics card.

Fittings Pack

Pics	Name	Qty	Used for
	#6 - 32*6 screw	8	Lock B/C, Lock 3.5" HDD
	#6 - 32*3/8 screw	4	HDD cage fan
	Stand-off socket	2	PU, P/ S fan
	Stand - off	10	M / B fan
	M/B screw	12	M / B fan
	#6 - 32*0 screw	7	HDD cage
	#6 - 32*4 screw	4	PSU
	Lock B/T	2	Side panel
	Case spacker	1	M / B Warning
	Cable tie	10	Cable management
	Anti-vibration pad	12	2.5" SSD
	M/B screw	12	2.5" SSD
	2.5" HDD adaptor	2	2.5" HDD
	Ø5*10 screw	8	Lock top fan Lock bottom fan
	M/B screw	40	ODD, 2.5" SSD
	Ø5*10.5 screw	4	Side fan
	stand-off	1	HDD cage

Silencio 652S

1/O Function panel installation guide

- Please refer to the illustrations in the motherboard user manual that describe USB 3.0, USB 2.0, and audio connectors to ensure that you connect the cables correctly. Connecting cables incorrectly may result in damage to your motherboard. Attempting to install anything other than matching connectors may result in damage and loss of function.
- On some motherboards, the connectors for USB 3.0, USB 2.0 and Audio are not the same as the drawing below. Please refer to your motherboard user manual for correct pinouts.
- The following illustration is a diagram showing the I/O connector.

I/O面板安装指南

- 请参考主板用户手册中的USB 3.0, USB 2.0 声音接头配件的图示，确保连接以下连接线的 3.0, USB 2.0, 和音频连接线。连接线错误可能会导致主板损坏。
- 一些主板的 USB 3.0, USB 2.0, 音频连接头与下图不同，实际请，参考相应的主板用户手册。
- 下图为I/O面板连接示意图。

Motherboard	Case Connector
USB 3.0 connector	USB 3.0 connector
USB_P3_P+ USB_P3_P- USB_P3_R- USB_P3_R+ GND Vbus	HD_TX_P3+ HD_TX_P3- HD_RX_P3- HD_RX_P3+ GND No Pin
USB 2.0 connector	USB 2.0 connector
USB-5V USB_P2- USB_P2+ GND No Pin	USB_P2- USB_P2+ GND No Pin
AUDIO	AUDIO connector
MIC2_R MIC2_JD PRESENCE# MIC2_L Line2_R Line2_JD Line2_L	MIC_R MIC_JD No Pin MIC_L HP_R HP_JD HP_L
Audio panel (HD audio) connector	AC'97 connector
PORT1 L PORT1 R PORT2 L PORT2 R SENSE_SEND PORT_C L PORT_C R	MIC2_L MIC2_R No Pin LINE2_L LINE2_R No Pin HP_L HP_R
Please check with your motherboard manual before installing.	Front Side (HDA) LED / RESET SW / HDD LED
	PLED+ PLED- RESET SW HDD LED PLED- PLED+

Silencio 652S

Silencio 652S

1.Diagram / 示意图

5.25" bay
3.5" bay
2.5" bay
3.5" bay
2.5" bay
3.5" bay
2.5